



Felco Vibratory Compaction Bucket with NPK Plate Compactors

Machine Weight (lbs.)	NPK Compactor	Standard Size (width x pin to tip)	Bucket Weight (lbs.)	Capacity (cubic yards)
18,000-38,000	C4	.20" x 42"	1,150	0.3
		.24" x 42"	1,225	0.3
		.24" x 48"	1,575	0.4
		.30" x 42"	1,275	0.3
		.30" x 48"	1,700	0.5
	C6	.30" x 48"	1,700	0.5
		.36" x 48"	1,950	0.6
38,000-50,000	C6	.24" x 60"	2,450	0.6
		.30" x 60"	2,625	0.9
		.36" x 60"	2,875	1.2
	C8	.30" x 60"	2,875	0.9
		.36" x 60"	2,875	1.2
	50,000-100,000	C6	.30" x 74"	3,350
		.36" x 74"	3,600	1.7
C8		.30" x 74"	3,500	1.2
		.36" x 74"	3,950	1.5
		.42" x 74"	4,250	1.8
C10		.42" x 74"	5,400	1.8

Notes: Not a recommended application chart. Machine and bucket weights are approximate. Machine weight multiplied by 7% equals maximum weight of acceptable bucket. Bucket lip measures 2" wider (1" per side) than bucket width. Every Felco Vibratory Compaction Bucket comes with a control valve to limit the flow and pressure to the motor. Additional features include a reverse-flow check to protect reversed line connections, and a cross-port check to provide a motor wind-down circuit.

Call Felco Industries for assistance in specific applications and prices.



800-221-5427
www.felco-ind.com
products@felco-ind.com